

# CEYAKRETE

construction chemicals & coatings

Manufactured by an  
**ISO 9001 2015**  
Certified Company

## TILE ADHESIVE

### DESCRIPTION

CeyaKrete Tile Adhesive is a cement based, polymer modified tile adhesive manufactured according to ISO 9001:2015 quality management system and internationally accepted raw material in compliance to international standards.

It is formulated for fixing a variety of tiles, mosaics, quarries, natural stones and marble on interior and exterior walls and floors.



TILE ADHESIVE  
ECO



VERY ECONOMICAL &  
HIGH WORKABILITY



TILE ADHESIVE  
PLUS +



ANTI-SLIP  
PROPERTIES



TILE ADHESIVE  
PREMIUM ★

TILE ON TILE



APPLICATION

### FEATURES

|  |   |   |   |
|--|---|---|---|
| Quick and Easy to use                    | ■ | ■ | ■ |
| Polymer Modified                         | ■ | ■ | ■ |
| For 2x2 Tiles                            | ■ | ■ | ■ |
| Stronger Bonding than Regular Cement     | ■ | ■ | ■ |
| Very Economical and High Workability     | ■ | ■ | ■ |
| For Wall and Floors                      | ■ | ■ | ■ |
| Good Adhesion Strength                   | ■ | ■ | ■ |
| Ideal for Porcelain and Ceramic Tiles    | ■ | ■ | ■ |
| Anti-Slip Properties                     |   | ■ | ■ |
| For Any Rough Surface                    |   | ■ | ■ |
| High Bonding Strength                    |   | ■ | ■ |
| Vitrified and Granite Tiles              |   | ■ | ■ |
| For Interior and Exterior Use            |   | ■ | ■ |
| Suitable for Any Wet Area                |   | ■ | ■ |
| Recommended for 2'x2' Tile Sizes & Above |   | ■ | ■ |
| Tile on Tile Application                 |   |   | ■ |
| Ideal for any Type and Size of Tiles     |   |   | ■ |
| Waterproofing Properties                 |   |   | ■ |



## SPECIFICATIONS

**COVERAGE:** 40 - 50 Sq.Ft  
(Depending on the surface condition)

**APPLICATION THICKNESS:** 3 - 5 MM

**WATER DEMAND:** 4 - 5 Liters

**PACK SIZE:** 25KG

**COLOUR:** Gray

**DRYING TIME:** 24 Hours from the time of fixing tile –  
for light foot traffic.

**POT LIFE:** 2 Hours from the time of mixing.

**SHELF LIFE:** Up to 6 months in unopened bags and  
stored in a cool dry elevated position.

**CERTIFICATION:** ISO 9001:2015 Quality Management  
System and Certified Test Reports.

**HEALTH & SAFETY:** It is recommended to use protective  
gloves, goggles and clothing during handling. If skin  
irritation occurs, seek medical attention promptly.

## INSTRUCTIONS FOR USE

### SURFACE PREPARATION

Before starting any work, make sure that the base is sufficiently flat to permit the specified flatness of finished tiling.

The entire surface should be clean, dry, fully cured and free from all dirt, grease, oils, waxes, curing agents and any other surface contaminants.

### MIXING AND APPLICATION

Mix CeyaKrete Tile Adhesive with clean potable water. Approximately 4-5 litres of water will be required for 25Kg of CeyaKrete Tile Adhesive.

Mix until a smooth slump-free consistency is produced.

- Dampen the surface prior to application.
- Apply CeyaKrete Tile Adhesive at a thickness of 3mm on the application surface (Wall / Floor).
- Press tiles firmly into position and make sure that all the tiles are well bedded with no voids in the adhesive.
- Do not allow the adhesive to dry prior to tiling (Max. 10 Mins).

Grouting should be carried out at least 12 hours after completion of tiling.

**DISCLAIMER:** The use of this product is beyond the manufacturer's control and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Specifications are subject to change without prior notice.

Member of



Group  
ESTB 1950

Subsidiary of Ceylon Rubber Industries Ltd.



**Ceyalac (Pvt) Ltd.**

#10 (1<sup>st</sup> Floor), School Lane,  
Colombo 03, Sri Lanka.

+94 11 7222252

+94 11 2507770

info@ceyalac.com

www.ceyalac.com

**Sales Hotline: 773 833 929**